

# S-4604

## Portable 3GSDI 1 to 4 Distributor

# SWIT

### Introduction:

The S-4604 is a portable 3G/HD/SD-SDI distributor. It supports 1 SDI input, and 4 SDI output, with embedded audio. There're Power/Input/Output status indicators to check the connection conditions and availability of distribution.

S-4604 is heavy duty housing design, protecting the BNC connectors well, and supplied various screw threads in the bottom, for convenient installing, and future accessories (battery mount, etc)



### Specifications:

| Input/Output |         |                     |
|--------------|---------|---------------------|
| Input        | BNC × 1 | 3G/HD/SD-SDI input  |
| Output       | BNC × 4 | 3G/HD/SD-SDI output |

  

| Video Format |                |  |
|--------------|----------------|--|
| SDI          | SMPTE-425M     | 1080p ( 60 / 59.94 / 50 )                |
|              | SMPTE-274M     | 1080p ( 30 / 29.97 / 25 / 24 / 23.98 )   |
|              |                | 1080i ( 60 / 59.94 / 50 )                |
|              | SMPTE-RP211    | 1080psf ( 30 / 29.97 / 25 / 24 / 23.98 ) |
|              | SMPTE-296M     | 720p ( 60 / 59.94 / 50 )                 |
|              | ITU-R BT.656   | 576i ( 50 )                              |
| SMPTE-125M   | 480i ( 59.94 ) |  |

  

| General             |  |
|---------------------|--|
| Power               | ≤ 2W                                     |
| Working Voltage     | DC 6-18V                                 |
| Working Environment | Temperature: 0°C-+70°C, Humidity:10%-90% |
| Dimensions          | 105 × 84 × 29 mm                         |
| Net weight          | 240g                                     |

### Features:

- ◆ Portable 3G/HD/SD-SDI 1 to 4 distributor
- ◆ 1 SDI input, 4 SDI output
- ◆ SDI re-clocking and amplifier
- ◆ Power/input/output status indicator
- ◆ Pole-tap 6-18V DC power input
- ◆ Heavy duty aluminium housing
- ◆ Bottom screw threads for installing

### SWIT Electronics Co., Ltd.

Website:www.swit.cc  
Email:contact@swit.cc  
Tel:+86 2585805753  
Fax:+86 2585805296

Distributed by: